# AVANTE® garage doors ALUMINUM AND GLASS CONSTRUCTION



America's Favorite Garage Doors®













Avante® is the perfect choice to modernize any home.

### STYLE AND CONSTRUCTION

- 2-1/8" aluminum frame provides a virtually maintenance-free, long-lasting door.
- Intellicore® polyurethane insulated rails and stiles (Model AXU).
- R-value 3.8/U-factor 0.86 (Model AXU when glazed with clear insulated glass).
- Many glass and panel options available.
- Section joint seal helps keep out air and water.
- Integral reinforcing fin provides increased strength and longevity (Available on double car models).
- Heavy-duty steel ball bearing rollers with nylon tires provide quiet operation. Calculated door section R-value is in accordance with DASMA TDS-163.

# **DOOR DESIGNS**





Additional sizes available for commercial door configurations Contact Clopay for details.

Model AXU (Insulated Glass)

Model AX (Insulated and Non-Insulated Glass

### **HARDWARE**



Attractive color-matched aluminum grip handles.

### FRAME/SOLID PANEL COLOR OPTIONS

Clear Aluminum (Anodized)

Standard White

Bronze (Painted)

Chocolate (Painted)

Bronze (Anodized)

Black (Anodized)

Dark Bronze (Anodized)

Due to the anodizing process, color variation may occur. The use of "Bronze (Painted)" is recommended for a more consistent bronze finish color. Custom colors available

## **GLASS/PANEL OPTIONS**











































(Satin Etched) \*Glass is tempered.

†5/16" clear laminate impact rated glass is available only on AXUW8/AXW8.

Clear Anodized Bronze Polygal (Color-matched to frame)

Glass available in single pane or insulated. Laminated and mirrored glass not available insulated. Panels can be aluminum to match the aluminum frame. Glass/acrylic panels may be combined with aluminum panels. Custom glass and colors available. See your Clopay Dealer for details. Acrylic windows require special cleaning. Never use products that contain ammonia or petroleum products to clean acrylic. Please visit www.clopaydoor.com/acrylic for complete details.

WINDCODE® AVAILABILITY CHART								
Common Door Widths		W1	W2	W3	W4	W5	W6	W8
Model AXU/AX	8', 9', 10' Wide Door	<b>S</b> +14/–14 PSF	<b>S</b> +18/–20 PSF	SELECT W4	<b>F S</b> +25/–25 PSF	<b>F S</b> +30/–30 PSF	<b>F S</b> +40/–44 PSF	<b>☞ F D S</b> +52/-58 PSF
	12' Wide Door	<b>S</b> +14/–14 PSF	<b>S</b> +18/–20 PSF	SELECT W4	<b>F S</b> +25/–25 PSF	<b>F S</b> +32/–32 PSF	<b>F S</b> +40/–44 PSF	<b>●F D S</b> +52/–58 PSF
	14' Wide Door	<b>S</b> +14/–14 PSF	<b>S</b> +18/–20 PSF	SELECT W4	<b>F S</b> +25/–25 PSF	<b>F S</b> +32/–32 PSF	<b>F S</b> +40/–44 PSF	<b>☞ F D S</b> +52/–58 PSF
	16' Wide Door	<b>S</b> +14/–14 PSF	<b>S</b> +18/–20 PSF	SELECT W4	<b>F S</b> +25/–25 PSF	<b>F S</b> +32/–32 PSF	<b>F S</b> +40/–42 PSF	<b>☞ F D S</b> +46/-52 PSF
	18' Wide Door	<b>S</b> +14/–14 PSF	<b>S</b> +18/–20 PSF	SELECT W4	<b>F S</b> +25/–25 PSF	<b>F S*</b> +30/–30 PSF	<b>F S*</b> † +36/–40 PSF	
	20' Wide Door	<b>S</b> +14/–14 PSF	<b>S</b> +18/–20 PSF	SELECT W4	<b>F S*</b> +25/–25 PSF	<b>F S*</b> +30/–30 PSF	<b>F S*</b> † +36/–40 PSF	

S Standard Windows Available T Texas Department of Insurance Approved

W Impact Windows Available

**D** Dade County Approved

Impact Rated

F Florida Approved